









VENTILI RUČNI NISKOTLAČNI REDUKCIONI

RADNI TLAK	VRSTA VENTILA	MATERIJAL	SIMBOL	
2 - 8 bara	Nepovratni	Ms/Ni		
	VRN N - U R1/8" Ms/Ni			
	VRN N - U R1/4" Ms/Ni			
	VRN N - U R3/8" Ms/Ni			
	VRN N - U R1/2" Ms/Ni			
1 - 10 bara	Prigušni	Ms/Ni		
	VRN P - G R1/8" L90K U R1/8" Ms/Ni			
	VRN P - G R1/4" L90K U R1/4" Ms/Ni			
	VRN P - G R3/8" L90K U R3/8" Ms/Ni			
1 - 10 bara	Prigušni nepovratni za cilindar	Ms/Ni		
	VRN PNC - G R1/8" L90K U R1/8" Ms/Ni			
	VRN PNC - G R1/4" L90K U R1/4" Ms/Ni			
	VRN PNC - G R3/8" L90K U R3/8" Ms/Ni			
1 - 10 bara	Prigušni nepovratni za ventil	Ms/Ni		
	VRN PNV - G R1/8" L90K U R1/8" Ms/Ni			
	VRN PNV - G R1/4" L90K U R1/4" Ms/Ni			
	VRN PNV - G R3/8" L90K U R3/8" Ms/Ni			

- Napomene:**
- Ovi niskotlačni ventili služe za regulaciju protoka zraka
 - Navedeni nepovratni imaju tlak otvaranja od 0,2 bara.
 - Podatke o dimenzijama pojedinih ovih ventila moguće je dobiti na upit.